

# RYOBI

## JIGGING REELS

**CARBON**  
FIBER DRAG

**ALUMINIUM**  
SPOOL

**7 BEARING**  
SYSTEM  
STAINLESS STEEL

**ALUMINIUM**  
BODY & ROTOR

**CNC**  
POWERKNOB  
& HANDLE



## SAFARI

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
5000A	4.9 : 1	750g	12kg	0.33-400 / 0.47-200

**2**  
SPEED  
NEW FOR 2012



**11+2**  
STAINLESS STEEL  
BEARINGS

## TURBO

**ALUMINIUM**  
BODY & ROTOR

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
18000	H: 2.9 : 1 L: 5.2 : 1	860g	15kg	0.5mm-250m
20000	H: 2.9 : 1 L: 5.2 : 1	900g	15kg	0.5mm-300m



**10+2**  
STAINLESS STEEL  
BEARINGS

**ALUMINIUM**  
BODY & ROTOR

**CNC HANDLE &**  
**RUBBER KNOB**

## CARNELIAN

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
18000	4.375 : 1	860g	15kg	0.5mm-250m
20000	4.375 : 1	880g	15kg	0.5mm-300m

# RYOBI

## SPINNING REELS



**WORM  
SHAFT**

**8+1  
STAINLESS STEEL  
BEARINGS**

**ALUMINUM  
BODY & ROTOR**

**EASY-FOLDING  
HANDLE**

### ZAUBER

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.1 : 1	280g	2.5kg	0.235-100 / 0.285-65
2000	5.1 : 1	280g	2.5kg	0.235-150 / 0.330-70
3000	5.0 : 1	305g	5kg	0.235-200 / 0.330-100
4000	5.0 : 1	315g	5kg	0.285-200 / 0.370-110

**WORM  
SHAFT**

**8+1  
STAINLESS STEEL  
BEARINGS**

**ALUMINUM  
BODY & ROTOR**

**EASY-FOLDING  
HANDLE**



### EXCIA

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	4.9 : 1	285g	6kg	0.20-130 / 0.30-55
2000	4.9 : 1	285g	6kg	0.20-200 / 0.30-90
3000	4.9 : 1	290g	6kg	0.20-300 / 0.30-130
4000	4.9 : 1	290g	6kg	0.25-290 / 0.35-130



**6+1  
STAINLESS STEEL  
BEARINGS**

**ALUMINUM  
BODY & ROTOR**

**EASY-FOLDING  
HANDLE**

**CARBON  
FIBER DRAG**

### APPLAUSE

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.1 : 1	280g	2.5kg	0.235-100 / 0.285-65
2000	5.1 : 1	280g	2.5kg	0.235-150 / 0.330-70
3000	5.0 : 1	310g	5kg	0.235-200 / 0.330-100
4000	5.0 : 1	320g	5kg	0.285-200 / 0.370-110
6000	5.0 : 1	580g	10kg	0.330-250 / 0.405-150
8000	5.0 : 1	595g	10kg	0.405-230 / 0.470-160

**5+1  
STAINLESS STEEL  
BEARINGS**

**ALUMINUM  
BODY & ROTOR**

**EASY-FOLDING  
HANDLE**

**CARBON  
FIBER DRAG**



### ZESTER

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.0 : 1	285g	6.0kg	0.235-100 / 0.285-65
3000	5.0 : 1	290g	6.0kg	0.235-200 / 0.330-100

**6 BEARING SYSTEM**  
STAINLESS STEEL

**ALUMINUM BODY**

**CNC HANDLE**  
6000-8000

**EASY-FOLDING HANDLE**  
1000-5000

**CARBON RING**



## ARCTICA

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.1 : 1	265g	2.5kg	0.235-150 / 0.285-100
2000	5.1 : 1	270g	2.5kg	0.285-130 / 0.330-100
3000	5.0 : 1	305g	5kg	0.330-140 / 0.370-120
4000	5.0 : 1	315g	5kg	0.330-170 / 0.370-140
5000	5.0 : 1	390g	7.5kg	0.370-170 / 0.405-130
6000	5.0 : 1	400g	7.5kg	0.370-200 / 0.405-170
7000	5.0 : 1	580g	10kg	0.405-210 / 0.435-180
8000	5.0 : 1	585g	10kg	0.435-220 / 0.470-180

**6 BEARING SYSTEM**  
STAINLESS STEEL

**CARBON FIBER DRAG**

**CNC HANDLE**  
6000-8000

**EASY-FOLDING HANDLE**  
1000-5000



## OASYS

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.1 : 1	276g	2.5kg	0.235-150 / 0.285- 80
2000	5.1 : 1	276g	2.5kg	0.285-110 / 0.330- 80
3000	5.0 : 1	315g	5kg	0.285-170 / 0.330-115
4000	5.0 : 1	320g	5kg	0.285-200 / 0.370-115
5000	5.0 : 1	400g	7.5kg	0.330-200 / 0.405-130
6000	5.0 : 1	405g	7.5kg	0.330-230 / 0.405-150
7000	5.0 : 1	580g	10kg	0.370-230 / 0.435-150
8000	5.0 : 1	585g	10kg	0.405-230 / 0.470-160

**7 BEARING SYSTEM**  
STAINLESS STEEL

**CARBON FIBER DRAG**

**ALLUMINIUM SPOOL**

**CARBON RING**

**CARBON HANDLE**



## KRIEGER

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.1 : 1	275g	2.5kg	0.205-150 / 0.235-115
2000	5.1 : 1	275g	2.5kg	0.235-155 / 0.285-110
3000	5.0 : 1	318g	5.0kg	0.235-220 / 0.285-150
4000	5.0 : 1	320g	5.0kg	0.285-200 / 0.330-150

**5 BEARING SYSTEM**  
STAINLESS STEEL

**CARBON FIBER DRAG**

**ALLUMINIUM SPOOL**

**EASY-FOLDING HANDLE**



## TRESOR

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000	5.1 : 1	275g	2.5kg	0.205-150 / 0.235-115
2000	5.1 : 1	275g	2.5kg	0.235-155 / 0.285-110
3000	5.0 : 1	318g	5.0kg	0.235-220 / 0.285-150
4000	5.0 : 1	320g	5.0kg	0.285-200 / 0.330-150

# RYOBI

**6+1**  
STAINLESS STEEL  
BEARINGS

**CARBON**  
FIBER DRAG

**ALUMINIUM**  
SPOOL

**EASY-FOLDING**  
HANDLE



## NAVIGATOR

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1500	5.1 : 1	264g	2.5kg	0.205-165 / 0.285-100
2500	5.1 : 1	266g	2.5kg	0.235-180 / 0.330-100
3500	5.0 : 1	312g	5.0kg	0.235-265 / 0.330-140
4500	5.0 : 1	315g	5.0kg	0.285-240 / 0.370-130
5500	5.0 : 1	322g	5.0kg	0.285-300 / 0.370-200
6500	5.0 : 1	325g	5.0kg	0.285-350 / 0.370-250



**6+1**  
STAINLESS STEEL  
BEARINGS

**CARBON**  
FIBER DRAG

**ALUMINIUM**  
SPOOL

## ECUSIMA

**EASY-FOLDING**  
HANDLE

Size	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
1000VI	5.1 : 1	262g	2.5kg	0.205-130 / 0.285- 65
2000VI	5.1 : 1	262g	2.5kg	0.235-150 / 0.330- 70
3000VI	5.0 : 1	302g	5.0kg	0.235-200 / 0.330-100
4000VI	5.0 : 1	302g	5.0kg	0.285-200 / 0.370-110
6000VI	5.0 : 1	552g	8.0kg	0.330-250 / 0.405-150
8000VI	5.0 : 1	555g	8.0kg	0.405-230 / 0.470-160



**CARBON**  
FIBER DRAG

**6+1**  
STAINLESS STEEL  
BEARINGS

**ALUMINIUM**  
BODY & ROTOR

**CNC HANDLE &**  
**RUBBER KNOB**

## NAXO

**SURF REEL**

Model	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
NAXO	3.9 : 1	718g	12kg	0.20-280 / 0.40-90



**4+1**  
STAINLESS STEEL  
BEARINGS

**CARBON**  
FIBER DRAG

**EASY-FOLDING**  
HANDLE

## PROSKYER

**SURF REEL**

Color	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
Black	5.1 : 1	690g	12kg	0.40mm-200m
Silver	5.1 : 1	690g	12kg	0.40mm-200m

# RYOBI

## BAITCASTING REELS



**9 BEARING SYSTEM**  
STAINLESS STEEL

**CARBON FIBER DRAG**

**ALUMINIUM FRAME & SPOOL**

**DOUBLE BREAK SYSTEM**

**SUPER LIGHT METAL REELS**

**CONTINUOUS ANTI-REVERSE**

## AQUILA

Model	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
R	6.3 : 1	215g	4.5kg	0.235-200 / 0.33-100
L	6.3 : 1	215g	4.5kg	0.235-200 / 0.33-100



**5 BEARING SYSTEM**  
STAINLESS STEEL  
**MACHINED ALUMINIUM FRAME**

**CARBON FIBER DRAG**

**SUPER LIGHT METAL REELS**

**CONTINUOUS ANTI-REVERSE**

## VARIUS

Model	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
DB300	5.8 : 1	290g	5kg	0.235-175 / 0.330-90



**8 BEARING SYSTEM**  
STAINLESS STEEL  
**MACHINED ALUMINIUM FRAME**

**CARBON FIBER DRAG**

**SUPER LIGHT METAL REELS**

**DOUBLE BREAK SYSTEM**

**CONTINUOUS ANTI-REVERSE**

## IXORNE

Model	Gear Ratio	Weight	Max Drag	Capacity (mm-m)
T300R	6.0 : 1	240g	4.0kg	0.235-200 / 0.33-100
T300L	6.0 : 1	240g	4.0kg	0.235-200 / 0.33-100

# RYOBI

## COOLER BOXES



驚異の軽さと独自のオープン機構。



Item	Capacity	Weight	Inside Dim.	Outside Dim.	FOB Price	MOQ
CNR200	20L	3.6kgs	420x210x242mm	509x295x310mm	--	100
CNR260	26L	4.2kgs	476x230x242mm	566x316x311mm	\$53.70	100



驚異の軽さと独自のオープン機構。

Item	Capacity	Weight	Inside Dim.	Outside Dim.	FOB Price	MOQ
CNX200	20L	3.7kgs	420x210x242mm	509x295x310mm	--	100
CNX260	26L	4.3kgs	476x230x242mm	566x316x311mm	\$61.50	100